

## NMS800

### DIGITAL READOUT SYSTEM

The NMS800 Digital Readout (DRO) is the newest in Newall's range of premium readouts. The DRO hosts many productivity enhancing features that will increase machine tool efficiency.

The NMS800, when matched with Newall's Spherosyn Serial and Microsyn Serial encoders, provides years of maintenance free, trouble free performance. Newall's inductive encoders are simple to install and designed to provide consistent accuracy and reliability even under the harshest workshop conditions.



### Features

- Clean, crisp PMVA LCD display with wide viewing angle
- Lathe, Mill and General Purpose functions
- Self Sensing Encoder Input
- Available in 2, 3, or 4 axes
- User definable function keys
- Linear and angular readings
- Stand alone or panel mounting

### Newall Advantage

- Backed by a company with over 50 years of proven reliability in manufacturing DRO systems & linear encoders
- Encoders carry an IP67 rating – All electronic and measuring components are sealed from the environment
- Continually provides accurate readings even under the harshest shop conditions
- No cleaning or maintenance required
- Tolerant to shock and vibration
- No glass or tape to break or scratch
- Ease of installation—no backer bar or machined surface required

### Warranty: 5 year mfg, 3 year No Fault\*

*\*USA & Canada Only*

*\*Varies by Region, Terms and Conditions Apply*

<b>General Purpose Functions</b>	<ul style="list-style-type: none"> <li>• 2, 3 or 4 axes configuration</li> <li>• Inch/mm conversion</li> <li>• Four user definable function keys</li> <li>• Absolute / Incremental operation</li> <li>• Axis pre-set / zero reset</li> <li>• Zero approach warning (graphic and audio)</li> <li>• Feed-rate display</li> <li>• Newall Encoder auto-detection</li> <li>• RPM display*</li> <li>• Angular readings*</li> <li>* requires rotary encoder</li> </ul>	<ul style="list-style-type: none"> <li>• Auto resolution detection*</li> <li>• Linear and segmented error compensation</li> <li>• Digifind / reference mark</li> <li>• Centre find (establish workpiece midpoints)</li> <li>• Programmable memory for datums and tools</li> <li>• Built in calculator</li> <li>• Undo function (move back up to eight steps)</li> <li>• USB port for loading new firmware and settings</li> <li>• Sleep mode</li> <li>• Scaling factor</li> </ul>
<b>Milling Specific Functions</b>	<ul style="list-style-type: none"> <li>• Bolthole circle / PCD calculations</li> <li>• Line hole / grid array calculations</li> <li>• Arc contouring</li> <li>• Pocket / island milling</li> <li>• Summing two encoders within the same plane</li> </ul>	
<b>Lathe Specific Functions</b>	<ul style="list-style-type: none"> <li>• Radius / diameter readings</li> <li>• Tool offset library (50)</li> <li>• Taper calculation</li> <li>• Vectoring (requires 3 axes)</li> </ul>	
<b>Encoder Compatibility</b>	<p>Serial Input: Newall Spherosyn &amp; Microsyn Serial, Propriety Signal <u>not compatible with previous Newall DRO Encoders (S2G/M2G).</u></p> <p>Digital (TTL) Input: Newall TTL Encoders. Many third party TTL encoders including Rotary.</p> <p>Contact your local sales representative for advise on compatibility.</p>	

<b>Display</b>	PMVA LCD Screen — 127mm x 122mm — Membrane keypad with audible tactile feedback
<b>Construction</b>	High pressure aluminium alloy cast front and rear panel
<b>Dimensions</b>	Height: 187mm (7.36"), Width: 306mm (12.04"), Depth: 46.6mm (1.83")
<b>Electrical Requirements</b>	Voltage of 100-240 VAC (47 – 63 Hz) to external PSU included

## SPECIFICATIONS

Encoder	Spherosyn Serial	Microsyn Serial
<b>Scale Travels</b>	52mm—13,000mm	50mm—1,000mm
<b>Scale Diameter / Material</b>	15.25mm / Stainless Steel	5.75mm / Carbon Fibre
<b>Reader Head Dimension</b>	112mm x 53.5mm x 28mm	75mm x 37.5mm x 23mm
<b>Overall Scale Length</b>	Travel Length + 258mm	Travel Length + 187mm
<b>Standard Cable Length</b>	3.5 metre and/or 7.0 metre with Armour and D Style Connector	
<b>Output Type:</b>	Newall Proprietary Serial	

### Compatible with the Spherosyn and Microsyn Serial Encoders, which have a number of advantages:

- IP67 environmental rating, fully submersible
- Withstands dust, dirt, oil and other harsh environment conditions
- No mechanical wear characteristics
- No more broken or scratched glass
- Requires no cleaning or regular maintenance



Designed and engineered in the

**UNITED KINGDOM**

Page 2

Datasheets provided by Sensata Technologies, Inc., its subsidiaries and/or affiliates ("Sensata") are solely intended to assist third parties ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, valuation, and judgment in designing Buyer's systems and products. Sensata datasheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular datasheet. Sensata may make corrections, enhancements, improvements, and other changes to its datasheets or components without notice.

Buyers are authorized to use Sensata datasheets with the Sensata component(s) identified in each particular datasheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATASHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATASHEETS OR USE OF THE DATASHEETS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATASHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com). SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY, AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA

### CONTACT US

#### Americas

Newall Electronics Inc.  
1803 OBrien Rd  
Columbus, OH 43228  
Tel: +1 614 771 0213  
[sales@newall.com](mailto:sales@newall.com)  
[newall.com](http://newall.com)

#### Rest of World:

Newall Measurement Systems, Ltd.  
Business Park, Unit 1 Wharf Way  
Glen Parva, Leicester LE2 9UT  
United Kingdom  
Tel: +44 (0) 116 264 2730  
[sales@newall.co.uk](mailto:sales@newall.co.uk)  
[newall.co.uk](http://newall.co.uk)